

Specifications

UNITS

GrindLazer 270



GrindLazer 390



GrindLazer 630



SPECIFICATIONS			
Part Number Unit only (*)	571002	571003	571260
Unit with X" 8 pt Flail Carbide Cutters, Complete Assembly	571018 (8")	571013 (10")	571262 (10")
Unit with X" 6 pt Miller Carbide Cutters, Complete Assembly	571021 (8")	571022 (10")	571265 (10")
Unit with 10" 5 pt Diamond Blades, Complete Assembly	-	-	571266
Unit with 5" 5 pt Diamond Blades, Complete Assembly	-	-	571267
Motor Engine – cc (HP)	Honda® 270 cm ³ (9)	Honda® 390 cm ³ (13)	Vanguard 630 cm ³ (21)
Removal rate (walk) – m ² /hr (sq ft/hr)	55 (600)	75 (800)	-
Removal rate (ride - LineDriver) – m ² /hr (sq ft/hr)	120 (1300)	160 (1700)	195 (2100)
Max. Cut Width – cm (in)	20 (8)	25 (10)	25 (10)
Weight – kg (lb)	135 (300)	140 (310)	154 (340)
FEATURES			
ProStart™ System	Extreme Duty Clutch	Extreme Duty Clutch	Extreme Duty Clutch
Air Cleaner	Cyclone	Cyclone	Heavy Duty Cyclone
Cut Direction	Forward	Forward	Reverse / "Up-Cut"
LineDriver*	Optional	Optional	Required (ProStart Safety Switch Interlock System)

* See page 18 and 39 for more information on LineDriver.

